BODY

TORQUE SPECIFICATION

SS0Z2-02

Part tightened		N·m	kgf⋅cm	ft·lbf
FRONT BUMPER		-	-	-
Front bumper cover x Body	Bolt:	8.3	85	74 in.·lbf
Front bumper cover x Body	Screw:	2.9	30	26 in.·lbf
Fog light x Front bumper cover		4.9	50	43 in.·lbf
Winch roller bracket x Front base member	Upper Side:	22	220	16
Winch roller bracket x Front base member	Lower Side:	28	290	21
Front bumper reinforcement x Front base member		28	290	21
Front base member x Winch assembly		22	220	16
Front base member x Body		99	1,010	73
Winch base bracket x Winch assembly		16	160	12
REAR BUMPER		-	-	-
Rear bumper cover x Body		20	200	14
Reflex reflector x Rear bumper cover		4.9	50	43 in.·lbf
Rear bumper reinforcement x Extension mounting bracket		13	130	9
Extension mounting bracket x Body		19	195	14
FRONT SEAT (Bench Type)		-	-	-
Rear seat track retainer x Seat Adjuster		20	200	14
Reclining connecting pipe x Seat adjuster		21	210	15
Seat cushion assembly x Seat adjuster	A Bolt:	20	200	14
Seat cushion assembly x Seat adjuster	B Bolt:	21	210	15
Seatback assembly x Outer seat adjuster		43	440	32
Seatback assembly x Reclining adjuster		43	440	32
Center armrest x Seatback assembly		37	380	27
Center armrest hinge x Center armrest		37	380	27
Center armrest hinge x Seatback assembly		37	380	27
Front seat adjuster x Body		37	375	27